ATLAS MANIPULATOR 7F

ENVIRONMENTLY FRIENDLY
NO HYDRAULIC SLIP-RING
CAN BE OPERATED AS A RATE MANIPULATOR



Description

The Atlas series of manipulators is suited to work with the highest performing vehicles under the most demanding conditions.

The Atlas manipulator is known as a strong and reliable manipulator which is a perfect alternative where you need strength, perfection, range, and not at least a low operation cost.

It is possible to setup the manipulator with several types of grippers. (7.8-in Four Finger / 11.2-in Four Finger / 6-in Parallel & 3 Finger Imenco Jaw)

Typical Operations

- ROV
- Subsea Wire handling
- Rough operations

Features

- Tough and Durable
- Environmentally friendly
- Compact Design
- Service & User Friendly
- Low operating cost
- Left-Hand & Right-Hand configurable options



SPECIFICATIONS

Atlas Manipulator 7F

Arm Specification

Fluid

Type Atlas Manipulator 7F Part number ARM-ATLAS Materials

Anodized Aluminum, Titanium, Stainless Steel

6-35 rpm

Mineral / Glycol, or Synthetic

Weight In Air: 73Kg / In Water: 50Kg

Standard Dept 6,500 msw 1.675 m Reach Lift at Full Extension 250 Kg Maximum Lift, Nominal 500 Kg Standard Gripper Opening 198 mm Grip Force, Nominal 205 Nm

Actuator Function

Wrist Rotate, Continuous

Azimuth Linear, 120° Shoulder Pitch Linear, 135° Elbow Pitch Linear, 135° Wrist Pitch Linear, 120° Wrist Yaw Linear, 120° Wrist Rotate Gerotor, 360° Gripper, Standard Linear, 198 mm

Hydraulic Specifications


207 Bar / 3000 PSI Max Pressure Available Flow 5.7 - 19 lpm Max. Fluid Temperature 54°C

Fuid Cleanliness ISO 4406 14/11


Hydraulic Connections

Line 1-15 15x JIC 04 Male


Gripper Options



6-in Parallel



7.8-in Four Finger Intermeshing



11.2-in Four Finger Intermeshing




IMENCO 3-Finger Jaw



SPECIFICATIONS


Atlas Manipulator 7F



TechnipFMC.com © Copyright TechnipFMC 2021.v 1.0. All rights reserved.

Schilling Robotics ATLAS 7P and 7R Manipulators $\mid 3$





Dimensions with Arm Stowed

