


SUBSEA RESERVOIR BASKET

2200 LITER
SUBSEA RESERVOIR
PUMP SYSTEM



Description

Subsea Reservoir Pump Basket is designed to reduce cost and HSE impact during pumping and injection operations by removing surface equipment from vessel deck.

The Reservoir Basket have 2 off 1100L fluid tanks that can be filled with two types of fluid prior to deployment. Hydraulic driven transfer pump are operated by an ROV, connected with a jumper hose, hotstab and receptacle. The large reservoir is ideally suited for any deep water applications to save time in operations requiring large volume of fluid.

Features

- Integrated transfer pump system
- ROV friendly valve control panel
- Two separate reservoirs
- Support different fluid types
- Guide funnel system
- DNV 2.7-1 Lifting certified

SPECIFICATIONS

SUBSEA RESERVOIR PUMP BASKET

General Technical Specifications

Type	Subsea Reservoir Pump Basket
Part Number	109721
Dimensions	mm 1850 x 1600 x 2470
Weight (in air)	kg ~3850

Hydraulic

Max. Input Pressure	Bar 207
Max. Output Pressure	Bar 350
Max. Input Flow	L/min 50
Max. Output Flow	L/min 30
Fluid tank size	Liter 2200 (2 off 1100)
Connection ROV pressure	JIC #8
Connection ROV return	JIC #8
Connection output pressure	JIC #6

General Features

Depth rating	MSW 3000
--------------	----------

