DIRTY WORK VALVE PACK

ROV TOOLING ISOLATED HYDRAULIC PUMP VP SYSTEM



Description

The Dirty Work Valve Pack (DW-VP) is a compact unit for subsea use in relation to tooling and pressure leak / test applications.

DW-VP contains 4x NG4 and 1x NG6 proportional valves for controlling ROV tooling. A motorpump (Dirty Work Pack) are flanged directly to the Valve Pack making it to a all-in-one system. The unique design are both cost efficient with regard to ROV interface and reduced connections (hoses/fittings) makes it a more reliable system due to HSE impact and leakages. Surface Software gives the operator control of both pump pressure and flow adjustment on all output lines.

Features

- Integraded Control System
- Digital flowmeter
- Digital pressure sensors
- 207 Bar pump supply (LP output)
- 690 Bar booster supply (HP output)
- Print of pressure test certification
- All in one system
- Coms. RS 232, 485 and Ethernet
- Small footprint and ease interface to ROV



SPECIFICATIONS DIRTY WORK VALVE PACK

General Technical Specifications

Dirty Work Valve Pack Type

Part Number 103271

mm 840 x 700 x 600 **Dimensions**

Weight (in air) ~90 kg

Electrical

VDC 24VDC Supply Voltage

Communication

RS 232, RS 485 and Ethernet 8PIN Glen Air G5506-1508-0004 Pigtail 1 meter

Hydraulic

Max. Input Pressure Bar 207

Max. Output Pressure LP line Bar 207 - 5 off Max. Output Pressure HP line Bar 690 - 1 off

Max. Input Flow L/min 75 Max. Output Flow L/min 40

Connection ROV pressure JIC #8 Connection ROV return JIC #8 Connection ROV drain JIC #6 Connection output pressure LP JIC #6 Connection output pressure HP JIC #4

General Features

MSW 3000 Depth rating



