

SOFTLINE CUTTER SL-80

SUBSEA SOFTLINE CUTTING
ROBUST AND USER FRIENDLY
CAN BE USED AT ANY WATER DEPTH



Description

The SL-80 cutter is a heavy-duty hydraulically operated soft and fibre line cutting tool. The open sided design allows for easy positioning on the line by ROV or diver and simple operation.

The Softsling Cutter is made of aluminium and stainless steel, and is therefore lightweighted and subsea friendly. It can be used at any water depth. The maximum cutting capacity is Ø80mm fibre rope.

Long blade life ensures that the tool maintenance is kept to a minimum.

Features

- Can be used at any water depth
- Diver or ROV operabel design
- Quick and efficient operation
- Service & User Friendly
- Corrosion resistant
- 2 Hydraulic ports (blade up, blade down)

SPECIFICATIONS

SLC-80 SOFTLINE CUTTER

General Technical Specifications

Type	SLC-80 Softline Cutter
Part number	SLC-80
Materials	Aluminium, Stainless Steel
Fluid	ISO32 Hydraulic oil
Weight	In Air: 15Kg / In Water: 10,5Kg
Dimension L x W x H	646 x 188 x 138mm

Hydraulic Specifications

Max. Operating pressure	690 Bar (External intensifier are following the SLC-80)
Swept volume (Cut stroke)	0,15 litres
Swept volume (Return stroke)	0,1 litres
Cutting capacity	Up to 80mm (3.15") diameter
Hyd Connection - Extract	JIC 04 Male - 690 Bar rated
Hyd Connection - Retract	JIC 04 Male - 690 Bar rated

