

STAB Ø43MM DP-20K- INTERV W/CV

PRESSURE RATED TO 1379 BAR(20K)
FIELD PROVEN
WITH CHECK VALVES



Description

The Ø43mm Hot Stab is made accordingly to API 17H Type 1 and comes in different types and configurations to suit a wide range of applications.

Ø8 bores for maximum flow and minimum pressure drop. Pressure tested to 1.5 x design pressure.

Typical pressure drop: 15 bar @50 L/min.

ROV or diver operated. Low mating force and easy entering, integrated flexjoint between stab and D-handle. Locking mechanism for stab available for critical applications.

Available in 1,2,3 and 4-port configurations for maximum flexibility. 1-4 ports receptacles, pressure stabs, dummy stabs and parking receptacles available.

Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust

Specifications

STAB Ø43 DP 20K INTERV W/CV

General Technical Specifications

Type	Hot Stab Ø43 DP 20K w/cv
Part No	N/A
Dimensions L x W x H	423 mm x 90 mm x 120 mm
Design Standard	5,5 kg

Hydraulic

Pressure Rated	1379 Bar
Hydraulic Input #1	MP 9/16"
Hydraulic Input #2	MP 9/16"

