

# STAB Ø43MM DP-5K- INTERV W/CV BSP 1/2

PRESSURE RATED TO 345 BAR(5K)  
FIELD PROVEN  
WITH CHECK VALVES



## Description

The Ø43mm Hot Stab is made accordingly to API 17H Type 1 and comes in different types and configurations to suit a wide range of applications.

Ø8 bores for maximum flow and minimum pressure drop. Pressure tested to 1.5 x design pressure.

Typical pressure drop: 15 bar @50 L/min.

ROV or diver operated. Low mating force and easy entering, integrated flexjoint between stab and D-handle. Locking mechanism for stab available for critical applications.

Available in 1,2,3 and 4-port configurations for maximum flexibility. 1-4 ports receptacles, pressure stabs, dummy stabs and parking receptacles available.

## Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

## Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust

# Specifications

STAB Ø43 DP 5K INTERV W/CV

## General Technical Specifications

Type

Hot Stab Ø43 DP 5K w/cv

Part No

N/A

Dimensions L x W x H

416 mm x 70 mm x 120 mm

Design Standard

4,2 kg

## Hydraulic

Pressure Rated

345 Bar

Hydraulic Input #1

BSP 1/2"

Hydraulic Input #2

BSP 1/2"

