

# RECEPTACLE Ø35MM QP- 10K-INTERV W/CV BSP 1/2" ID 8MM

PRESSURE RATED TO 690 BAR (10K)  
FIELD PROVEN  
WITH CHECK VALVES



## Description

Receptacle and hot stabs come with integrated check valves as a default for minimum fluid spill and water ingress during operations.

The Receptacle and Hot Stabs are designed to maximize the flow capacity and minimum pressure drop.

Built after API17H, Type 1 design. Available in 1,2,3 and 4-port configurations for maximum flexibility. 1-4 Ports Hot Stabs, Dummy Stabs and Parking Receptacles are available. The Hot Stab/Receptacle system can also be fitted with a lock-system.

## Typical Operations

- ▣ Topside Tooling Applications
- ▣ Subsea Operations
- ▣ Function Testing
- ▣ Flushing

## Features

- ▣ Field Proven
- ▣ Integrated with Check Valves
- ▣ Compact Design
- ▣ Service and User Friendly
- ▣ Robust

# Specifications

Ø35 ROV RECEPTACLE QP-10K-INTERV W/CV 1/2" BSP

## General Technical Specifications

Type	ROV Receptacle
Part Number	N/A
Dimensions L x W x H	169.5 mm x 79,5 mm x 79,5 mm
Weight in air	4,8 kg

## Hydraulic

Max Input Pressure	690 Bar
Max Output Pressure	690 Bar
Max Input Flow	25 L/min
Max Output Flow	25 L/min

Connection Port 1	1/2" BSP
Connection Port 2	1/2" BSP
Connection Port 3	1/2" BSP
Connection Port 4	1/2" BSP

