HYDRAULIC HOSE REEL

6 HOSE UMBILICAL 8 FUNCTION SLIP RING Ø52" BY 42" WIDE DRUM



Description

The Hydraulic Hose Reel is equipped with a 6 hose umbilical and a 8 function slip ring. This is 213 meters long and can handle up to 345 Bar operating pressure.

The Hose Reel is operated with a small hydraulic motor. Rotary manifold for easy use.

Typical Operations

- Prime Gated Shear Cutter
- Downline operations

Features

- □ Ø52" by 42" wide Drum
- 213m Capacity
- 6 Hose Umbilical



The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

SPECIFICATIONS

Hydraulic Hose Reel

General Technical Specifications

Type Dimensions L x W x H Weight in air Capacity Max Operating Pressure Hydraulic Hose Reel 2500 mm x 2500 mm x 2650 mm 3493 Kg 213 m 345 bar

The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

