DYNASET 220 BAR JETTING

HIGH PRESSURE JETTING NOZZLE 220 BAR



Description

The Dynaset 220 Bar jetting pump is used as a field proven, user friendly and highly effective tool for subsea cleaning from ROV.

The high pressure jetter is based around the Dynaset HPW pump and is capable of jetting at 220 bar with the standard nozzle fitted.

The system is supplied with all necessary components, hoses for connection to ROV, lance hose, manipulator handle and turbo nozzle.

Typical Operations

- Cleaning Operation
- High Power Jetting

Features

- Max pump pressure 220 bar
- □ Max pump flow 50 L/min
- Jetting and gun included
- Round and Flat nozzle included

envirent

Compact and low weight

The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

SPECIFICATIONS

DYNASET 220 BAR JETTING KIT

General Technical Specifications

Туре	Dynaset 220 Bar Jetting Kit
Part Number	HPW-220
Dimensions L x W x H	575 mm x 570 mm x 540 mm
Weight in air / submerged	~35 kg / ~30 kg

Hydraulic

Max Input Pressure	207 Bar
Max Output Pressure	220 Bar
Max Input Flow	70 L/min
Max Output Flow	50 L/min
Connection ROV Pressure	JIC #12
Connection ROV Return	JIC #12

Technical

Depth Rating

MSW 3000

The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, post@envirent.no

