

HYDRAULIC NUT-SPLITTER SINGLE ACTING

HYDRAULIC

M6-M48

6-93 TE CUTTING CAPACITY



Description

The Single Acting Nut Splitter can easily cut through and break frozen or stuck nuts. Nut Splitter comes in various sizes to fit most nuts.

A ROV handle is mounted for easily maneuvering with your ROV. The tool is delivered with an MiniBooster rated up to 690 bar. Chisel can be re-sharpened multiple times.

Typical Operations

- ▣ Splitting nuts

Features

- ▣ MiniBooster intensifier
- ▣ ROV handle
- ▣ Various sizes

Specifications



Hydraulic Nut Splitter

Description

Type	Cutting Tool
Part Number	NS-SA-xxxx-xx
Dimensions L x W x H	See table below
Weight	See table below

Hydraulic

Max Input Pressure (from MiniBooster)	690 Bar
MiniBooster Ratio	1 : 4
Max. Input Pressure MiniBooster	172,5 Bar
Max. Input Flow MiniBooster	14 L/min
Connection A	JIC 06
Connection B	JIC 06

MODEL	Capacity (T)	A	B	C	D	E	F	G	H	K		
NS1319	6	40	190	7	19	121	28	55	48	57	11	1
NS1924	10	54	217	10	26	146	40	55	62	60	17	2
NS2432	15	64	245	13	29	178	51	55	72	71	40	3.2
NS3241	21	75	260	17	36	205	66	55	88	77	62	4.7
NS4150	34	94	310	21	45	244	74	55	105	90	123	8.5
NS5060	49	106	335	23	54	289	90	55	128	100	191	13
NS6075	93	156	410	26	72	365	110	55	181	124	650	34

S	N
M6-M12	13-19
M12-M16	19-24
M16-M22	24-32
M22-M27	32-41
M27-M33	41-50
M33-M39	50-60
M39-M48	60-75

