

17T SUBSEA BASKET



Description

The 17-tonne Subsea Basket features an engineered design incorporating a foldable lifting beam and drop-down access doors.

These design elements, combined with a high payload capacity and an expanded footprint, provide enhanced operational flexibility and versatility. The basket is suitable for deployment across a broad range of subsea operations and handling requirements.

Key benefits include a single lifting point, high payload capacity, and integrated forklift handling provisions.

Certified according to DNV 2.7-3 R60

Typical Operations

- ▣ Subsea Lifting
- ▣ Transportation
- ▣ Deploying Tools

Features

- ▣ Drop-down doors with ROV-operated locks provide secure access and enhanced HSE during loading and unloading.
- ▣ Foldable lifting Beam
- ▣ Grabber Bars to enable ROV friendly handling of equipment
- ▣ Removable side walls and drop-down doors enable use as a lifting platform, clump weight, or equipment foundation.
- ▣ Optional: Top Hatch.

▣ The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, sales@envirent.no

SPECIFICATIONS

17T SUBSEA BASKET

General Technical Specifications

Type	Lifting
Part Number	17T
Internal Dimensions L x W x H	5000 mm x 2570 mm x 950 mm
External Dimensions L x W x H	6000 mm x 3200 mm x 3600 mm
External Dimension Folded L x W x H	6000 mm x 3200 mm x 6100 mm
Weight in air (Gross Weight)	22000 kg
Weight in air (Tara Weight)	5000 kg
Payload	17000 kg
Material	Carbon Steel, GRP and Aluminium



■ The specification details are illustrative for marketing purpose only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement. Envirent AS, Robotvegen 16, 4340 Bryne, +47 477 77 500, sales@envirent.no